Garage Doors MADE BY RYTERNA



Content

TL&R40 RIB	1
TL&R40 MIDRIB	1
TL&R40 FLUSH	1
TL&R40 CASSETTE	1
TL&R40 SLICK	1
TL&R40 SLICK PLUS	2
TL&R40 MICRORIB	2
TL&R40 MACRORIB	2
TL&R40 TOPRIB	2
SIDE DOORS	2
TWO LEAF SWING DOORS	2
PASS DOORS	3
DÉCOR APPLIQUES	3

STAINLESS STEEL	WINDOWS	3
ACRYLIC DOUBLE	E GLAZED WINDOWS	Э
FULL VISION PANE	ELS	3
HARDWARE TYPE	ER40	Э
HARDWARE TYPE	ETL	3
ACCESSORIES		4
THE SIDE SLIDING	SECTIONAL DOOR	4
HARDWARETYPE		4



Unlimited creativity

Freedom to express your ideas in many ways.





Think outside the box

A diversity of modern designs, variety of colours, number of features. Whether to merge with the general architecture, or to create a statement in your neighbourhood. Long-lasting solutions and no halfway measures with the quality.







ô



Look and functionality

Straight lines and square shapes for a minimalistic, contemporary view or just a simple solution to cover your garage space from the outside.





TL&R40 | RIB

Horizontal ribs every 10 cm give this door a light yet sturdy appearance.

This is a door with a contemporary appearance that looks good in any architectural setting.

Wood Rib comes in 4 different natural looking wood finishes -Golden Oak, Old Oak, Dark Oak and Mahogany.

Rib doors are often combined with full-vision aluminium panels available in any RAL colour and also a golden oak finish.

Rib type doors are best in special oversized openings – they can be made up to 10 metres wide.



Panel styles:



(woodgrain)

Wood images:









(woodgrain) (woodgrain) (woodgrain)







TL&R40 | MIDRIB



The Midrib style door, grooved in the middle of each panel, gives the impression of solid timber boards. This is a popular style all over Europe. Midrib panels are available in woodgrain, stucco and smooth patterns, in standard white RAL 9016 or any other RAL colour. The Wood Midrib style door comes with a smooth, non-embossed surface, coated with a natural wood looking UV proof PVC covering. Mahogany, Golden oak, old oak and light oak finishes are available.

Around 200 RAL colours are available.

Panel styles:







RAL 9016 (woodgrain)

RAL 9016 (stucco)

RAL 9016

Wood images:







Old Oak (smooth)

Light Oak (smooth)





TL&R40 | FLUSH

The Flush door design with its smooth panels, woodgrain or stucco embossed surfaces offers a look that complements both period and modern homes. The look is subtle and understated but is impressive when combined with stainless steel windows.

Flush type doors are available in standard RAL 9016 white and RAL 7016 grey, or any RAL colour.



Panel styles:



RAL 9016 RAL 9016 (woodgrain) (stucco)

TL&R40 | Flush







L&R40 | Cassette

TL&R40|CASSETTE



The Panelled Cassette door has stylish Georgian type rectangular panels beautifully sculptured with crisp lines and details on the outer surface. The cassette door is mainly suited to the traditional or country style home. Where there is timber decoration to the house the panelled cassette door, coated with a natural looking golden oak finish, will look perfect.







RAL 9016 (woodgrain)





Golden Oak (woodgrain)





TL&R40 | SLICK



The top of the range Slick style door offers a totally flat and smooth panel surface. Double outside steel thickness is used to give this door a really solid look and performance. This door fits aesthetically in any style of building. The smooth surface is great for combining with stainless steel windows or decals.









FL&R40 | Slick





RAL 7016 (smooth)



18



TL&R40 | SLICK PLUS

Exclusively coated.

Smooth doors we call 'Slick Plus' are an original idea with an impressive Copper, Anthracite, Stainless Steel and Golden Oak finish.

Impressive looking Slick-Plus coating - Golden Oak, Stainless Steel, Copper, Anthracite Grey (similar RAL 7016), Anthracite Black (similar RAL 9005) and Anthracite Green (similar RAL 6009).





Panel styles:



Golden Oak (smooth)



Stainless Steel



(smooth)



(smooth)





Anthracite Grey Anthracite Black Anthracite Green (smooth)



(smooth)



Anthracite Black Anthracite Green (smooth)



Golden Oak (smooth)



Stainless Steel (smooth)



Copper (smooth)



Anthracite Grey (smooth)



(smooth)



CONTENT



L&R40 | Microrib

TL&R40 | MICRORIB

The Microrib. The strength of this modern style door lies in its exceptional smooth surface, slightly waving every 5 mm. These unique panels can be combined with stainless steel windows for a creative and practical appearance.

Microrib doors come in standard RAL 9016 white or finished in other RAL colours.









RAL 9016 (smooth)








TL&R40 | Macr

TL&R40 | MACRORIB



The Macrorib door comes in standard RAL 9007 or in any other RAL colours.







RAL 9007 (stucco)







TL&R40 | Toprib

TL&R40 | TOPRIB



Finally, the latest product from Ryterna. We call it the TOPRIB. The double groove design is one of the most discernible styles in the market. The extra thickness provides a high quality, smooth panel surface. Three double lines dividing panels make this door stand out from similar products.

A beautiful, contemporary door.



RAL PEARL colours.





RAL 9016 (smooth)



Door frame can be ordered with or without edge profiles.



Without edge profiles





Easy fitting to side walls.



Frame dimensions.



Ryterna side doors are equipped with sliding door




Handle standard colours: silver, black, white. Other colours upon request.



SIDE DOORS

Ryterna manufactures tailor made side doors to match the garage door you choose. Ryterna side doors are made of PU, insulated 40 mm panels, surrounded with aluminium profiles and 'all-round' rubber seals. Side door windows are aligned with sectional door panels or windows.

Double leaf entry doors available on request.







Two leaf swing doors

Side

TWO LEAF SWING DOORS

Two leaf doors are recommended when the opening is wider than 1300 mm.

When used as a garage door, S4 lowstep profile (see page 28) is recommended.












PASS DOORS

When additional entry is required and there is no space for a side door, the wicket door fitted into the garage door could be an option. Wicket doors are supplied as standard with a door closer, lock and handle. You can choose the standard pass door or a new version with a low step, which is more convenient to get your bicycle or wheelchair through.









DÉCOR APPLIQUES

Whilst a wide range of decors are offered by Ryterna, we welcome your personal artistic design to make your garage door an object of your own creativity. Forward your design and we will apply them to the garage door when possible. You can create the design to match your standard entrance door or similar. All we require are the measurements of the door you wish to match the design to and a picture of the existing door to copy the design.

Appliques are made in stainless steel and RAL coloured plate.









STAINLESS STEEL WINDOWS

Using windows from our stainless design range will give your garage door a contemporary and unique appearance. Use our recommended designs or create your own.



MAXI 315 x 315 mm MIDI 235 x 235 mm MINI 155 x 155 mm 805 x 155 mm



MAXI Ø 315 mm MIDI Ø 235 mm MINI Ø 155 mm



Acrylic double glazed











ACRYLIC DOUBLE GLAZED WINDOWS

A range of windows and decorative inserts are offered to add distinction to any home. Acrylic window frames and inserts can be coloured to match your door or existing colours on your house.



FULL VISION PANELS



Full vision panels can be provided in an anodized aluminium frame, with matching colours or in RAL golden oak effect to match existing windows and doors.







HARDWARE TYPE R40

R40 sectional garage doors have been designed to be a consumer and installer friendly door – with its minimised headroom and side-room it is ideal for new houses as well as for replacing old garage doors. The made to measure and factory pre-assembled R40 door is very easy and fast to install.

irregularities, tightly closing the

garage door.

A safe and reliable track system All Cable pulleys are covered to protect from the possibility of injury. Rubber weather seals will ensure the door is properly closed from the bottom to the top. They also help to protect fingers. The bottom seal works as a minor shock-absorber and eliminates minor floor

Tension springs assembly. Side mounted, under-track mounted or top mounted springs are factory pre-installed and covered to grant an easy installation and safe operation. The four spring system protects the door even in the case of one spring failure.

Ball bearing rollers. Nylor coated rollers guarantee longer service and quiet operation.

Finger protection. Anti-pinching panels prevent the possibility of injury while operating the door.

Side hinges with an adjustable roller carrier ensure the most efficient performance and keep it from derailing.

A convenient internal handle is located at the bottom corner and is very useful in case of power failure.

HARDWARE TYPE R40


Longer durability


R40 track system comes fully preassembled with tension springs, cables and accessories. The door with R40 type hardware is easily installed. Maximum R40 door measurements 3000 x 2500 mm.


Technical specifications in accordance to EN 13241-1


Safety features in accordance with EN 13241


Tension spring Ball bearing rollers Safe track system Reinforced frame with side finger protection. Doors are tested to meet CE norm 89/107/EC Anti-pinching panels from the inside and outside. Insulation infill - CFC free PU foam.





















HARDWARE TYPE TL

Components of our sectional garage doors have been developed and tested under the most demanding industrial conditions. Over decades of operations we have perfected every detail of our doors. We call it Intelligent Quality Control and it is a continuous process.

Torsion springs. Every garage door comes with a spring break protection mechanism for each spring in the system.



Ball bearing rollers. Nylon coated rollers guarantee longer service and quiet operation.



Rubber weather seals at the sides will ensure the door is properly closed from the bottom to the top. They also serves as finger protection.

The bottom seal works as a mino shock-absorber and eliminates minor floor irregularities, tightly closing the garage door.



Finger protection. Anti-pinching panels keep fingers safe.



Side hinges with an adjustable roller carrier ensure most efficient roller performance and keep them from derailing.



A convenient handle is fitted at the bottom corner and is very useful in case of power failure.

HARDWARE TYPE TL


Longer durability


TL track system with torsion springs provides perfect counterbalance for a sectional door of any size or width. For challenging installation conditions we have developed LHR-FM and LHR-RM hardware types.

Technical specifications in accordance with EN 13241-1


Safety features in accordance with EN 13241


Industrial grade torsion springs Ball bearing rollers Safe track system Reinforced frame with side finger protection Doors are tested to meet CE norm 89/107/EC Anti-pinching panels from the inside and outside. Insulation infill - CFC free PU foam.


















CONTENT



ALU frame (front installation) Lintel + post. Lintel 120 mm (suitable for LHR RM and R40). Lintel 180 mm (suitable for LHR FM). Posts 100 mm.



ALU Lintel profile only. 120 mm; 180 mm.



Reinforced lintel profile for fitting to the ceiling. 40 x 40 x 90 x 3200 mm

Lintel profile with weatherseal 120 x 40 mm. Standard black, also available in matching door colour and structure.



Decorative angle 100 x 40 mm. Available in woodgrain golden oak and woodgrain white.



UNIVERSAL HANDLE

White door leaf parts (hinges, top and bottom brackets) and even all track system coated in white are available as an option.



DOOR HANDLE

Most of our doors are electrically operated, but for those that will be used manually Ryterna offers lock and handle kits.





The Side Sliding Sectional

THE SIDE SLIDING SECTIONAL DOOR

- The door is designed for an elegant look, convenient use and long life.
- Variety of panel designs smooth, ribbed or embossed.
- Door can be partially opened for pass door use, or just a half door opening. Convenient and thermally efficient.
- Corrosion-resistant and low maintenance aluminium hardware, top quality carriages and no-spring system provide quiet and trouble free operation.
- 40 mm PU panels and brush seals along the perimeter provide high thermal insulation.

FV - filling

■ Low ground rail with no requirement for built in floor channel.

Types of door sections:

CASSETTE



Standard colour:



Other painted colours similar to RAL palette.

Panel styles:







.6 RAL 9016 in) (stucco)




RAL 9016 (smooth)







45





www.ryterna.eu

DEALER: